

DuPont™ Cyrel® DFUV

Highest Print Quality with UV Inks

Applications

- Pressure sensitive labels
- Self-adhesive labels
- Shrink wrap labels
- Wrap around labels
- Tickets/tags/boards



Cyrel® FAST DFUV is a thermal process plate for use with UV inks that comes to color quickly and prints smooth and dense solids, without compromising dot gain, highlights and resolution. DFUV is specifically designed for shorter, narrow web print runs using UV inks on high priced stock, where minimizing the startup waste is essential. Cyrel® DFUV comes up to color almost immediately and is designed for very fine screens.

Product Features

- Comes up to color very quickly and predictably for reduced setup time and reduced material waste
- Extremely rapid access time thanks to thermal plate processing where no drying step is needed
- High and uniform/smooth UV ink transfer for outstanding tonal reproduction
- Very high resolution capability enabling > 200 lpi screens
- Excellent for printed security features and micro text down 1 pt
- High durability on press
- Exceptional thickness uniformity with no plate swelling during platemaking
- High resistance to ozone and white light results in excellent storage capability

Printing Ink and Solvent Compatibility

Cyrel® DFUV is specifically designed for use with UV inks due to its excellent compatibility and resistance. Also offers comparable compatibility with solvent-based, and water-based inks.

Platemaking

The Cyrel® FAST thermal developer allows the production of Cyrel® FAST finished plates in less than one hour, making it the ideal just-in-time platemaking system for a market that

demands quick turnaround at the highest possible quality. The Cyrel® FAST thermal developer delivers outstanding plate quality and uniformity. This processor has the ability to produce a finished plate without solvent washout. The Cyrel® ECLF for exposing and light finishing plates is available to complement the Cyrel® FAST thermal developer.

Process of Use

DuPont™ Cyrel® DFUV is designed to work with Cyrel® FAST thermal platemaking. Expose the plate through the back to establish the floor and minimize sensitivity. Back exposure varies according to relief required. Remove the protective coversheet, and image the plate with a Cyrel® Digital Imager (CDI). Expose the front of the plate surface. Process the plate in the Cyrel® FAST thermal developer. Finish the plate in a light finisher to eliminate surface tackiness. Post-expose the plate to ensure complete polymerization.

Mounting

Cyrel® Microflex mounting devices are recommended for mounting Cyrel® DFUV plates. The double sided adhesive should first be applied to the cylinder or sleeve – not the plate – to ensure easier and precise laydown. The polyester base will maintain accurate register even with large plates.

DuPont™ Cyrel® DFUV

Highest Print Quality with UV Inks

Storage—Raw Material

Store unexposed plates in a cool area (40–90°F, 4–32°C), away from direct sources of heat. Humidity control is not required. Cyrel® DFUV is foam interleaved to provide maximum protection of the plate after manufacture, and during transportation and storage. Plates should be stacked flat. Plates should not be exposed to direct sun-light or excessive white light. Continuous exposure to very high ozone concentrations should be avoided.

Handling – Raw Material

Like all photopolymer plates, Cyrel® DFUV plates should be handled under UV free light; e.g. fluorescent tubes covered with amber sleeves.

Storage – Finished Plates

After printing, plates should be thoroughly cleaned with a compatible solvent before storing. They may be stored on cylinders, sleeves or demounted and stored flat.

Technical Data

	Thickness	Durometer	Image Reproduction	Min. Positive Line Width	Min. Isolated Dot Size	Relief Depth
Cyrel® DFUV 45	1.14 mm / 0.045"	76 Sh A	1–98% / 80 L/cm/200 lpi	0.100 mm / 4 mil	200 µm	max. 0.55 mm / 0.022"
Cyrel® DFUV 67	1.70 mm / 0.067"	73 Sh A	1–98% / 80 L/cm/200 lpi	0.100 mm / 4 mil	200 µm	max. 0.65 mm / 0.026"

DuPont Advanced Printing brings together leading technologies and products for the printing and package printing industries. DuPont™ Cyrel® is one of the world's leading flexographic platemaking systems in digital and conventional formats, including DuPont™ Cyrel® brand photopolymer plates (analogue and digital), Cyrel® platemaking equipment, Cyrel® round sleeves, Cyrel® plate mounting systems and the revolutionary Cyrel® FAST thermal system.



cyrel.com/na

For more information on DuPont™ Cyrel® or other DuPont products, please visit our website.

The information provided in this data sheet corresponds to our knowledge on the subject at the date of its publication. It may be subject to revision as new knowledge and experience becomes available. This information is not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of our products for your particular purposes. Since we cannot anticipate all variations in end-use and disposal conditions, DuPont makes no warranties and assumes no liability in connection with any use of this information. It is intended for use by persons having technical skill, at their own discretion and risk. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent right.

DuPont™, the DuPont Oval Logo, and all products, unless otherwise noted, denoted with ™, SM or ® are trademarks, service marks or registered trademarks of affiliates of DuPont de Nemours, Inc. Copyright © 2020 DuPont de Nemours, Inc. All rights reserved

PDS-NA0038-EN (11/20)